

SAV Model B77, Double Eccentric Butterfly Valve Class Code/ Ref. # / Breakdown

B77 - Model No.	XXXX - Size	XX - Flange Configuration	XX Actuation	X - Opening Direction	X Testing Pressure	X Test Direction
	0600 - 24"	FF - FLxFL	AG - Above Ground	L - Open Left	L - 150 PSI	1 - Single
	0750 - 30"	MM - MJxMJ	BG - Below Ground	R - Open Right	H - 250 PSI	2 - Bi-directional
	0900 - 36"		BS - Bare Shaft	B - Both *		
	1050 - 42"					
	1200 - 48"					

* - Only on bare stem valves

MODEL B77, DOUBLE ECCENTRIC BUTTERFLY VALVE ACRONYMS

:ANSI - American National Standards Institute
 ASME - American Society of Mechanical Engineers
 AWWA - American Water Works Association
 DI - Ductile Iron
 EPDM - Ethylene Propylene Diene Monomer
 FL - Flange
 MJ - Mechanical Joint
 WAF - Wafer
 FF - Flange x Flange
 MF - Mechanical Joint x Flange
 WW - Wafer


Type

**Model B77/FF/RGB-1
DOUBLE ECCENTRIC
BUTTERFLY VALVE
To AWWA C504**

Flanged end to ANSI B 16.1

Class 125

Ductile iron
250 PSI
Size 24"-48"



SAV Ref. #

Size

**Weight
kg lb**

**Price
US \$**

B77-0600-FF-RGB-H	24"	425	936	11,808
B77-0750-FF-RGB-H	30"	764	1684	20,280
B77-0900-FF-RGB-H	36"	1130	2490	24,600
B77-1050-FF-RGB-H	42"	1685	3715	38,100
B77-1200-FF-RGB-H	48"	2282	5029	49,140


Specify above ground, or below ground intallation when ordering

**Model B77/FF/RGB-2
DOUBLE ECCENTRIC
BUTTERFLY VALVE
To AWWA C504**

Flanged end to ANSI B 16.1

Class 125

Ductile iron
250 PSI
Size 24"-48"
Bi-Directional Testing



B77-0600-FF-RGB-H2	24"	425	936	12,989
B77-0750-FF-RGB-H2	30"	764	1684	22,308
B77-0900-FF-RGB-H2	36"	1130	2490	27,060
B77-1050-FF-RGB-H2	42"	1685	3715	41,910
B77-1200-FF-RGB-H2	48"	2282	5029	54,054

Specify above ground, or below ground intallation when ordering

Type	SAV Ref. #	Size	Weight kg lb		Price US \$
Model B77/MM/RGB-1 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Mechanical Joint ends Ductile iron 250 PSI Size 24"-48"					
	B77-0600-MM-RGB-H	24"	429	944	11,808
	B77-0750-MM-RGB-H	30"	756	1667	20,280
	B77-0900-MM-RGB-H	36"	1160	2557	24,600
	B77-1050-MM-RGB-H	42"	1720	3790	38,100
	B77-1200-MM-RGB-H	48"	2309	5111	49,140
	Specify above ground, or below ground intallation when ordering				
Model SeB77/MM/RGB-2 DOUBLE ECCENTRIC BUTTERFLY VALVE To AWWA C504 Mechanical Joint ends Ductile iron 250 PSI Size 24"-48" Bi-Directional Testing					
	B77-0600-MM-RGB-H2	24"	429	944	12,989
	B77-0750-MM-RGB-H2	30"	756	1667	22,308
	B77-0900-MM-RGB-H2	36"	1160	2557	27,060
	B77-1050-MM-RGB-H2	42"	1720	3790	41,910
	B77-1200-MM-RGB-H2	48"	2309	5111	54,054
	Specify above ground, or below ground intallation when ordering				