

SAV Model B88, Concentric Butterfly Valve Class Code/ Ref. # / Breakdown

B88 - Model No.	XXXX - Size	XX - Flange Configuration	XX Actuation	X - Opening Direction	X Testing Pressure	X Test Direction
	0080 - 3"	FF - FLxFL	AG - Above Ground	L - Open Left	L - 150 PSI	1 - Single
	0100 - 4"	MF - MJxFL	BG - Below Ground	R - Open Right	H - 250 PSI	2 - Bi-directional
	0150 - 6"	MM - MJxMJ	LV - Above Ground/Lever	B - Both *		
	0200 - 8"	WW - WAFER	BS - Bare Shaft			
	0250 - 10"					
	0300 - 12"					
	0350 - 14"					
	0400 - 16"					
	0450 - 18"					
	0500 - 20"					
	0600 - 24"					

* - Only on bare stem valves

MODEL B88, CONCENTRIC BUTTERFLY VALVE ACRONYMS :

- ANSI - American National Standards Institute
- ASME - American Society of Mechanical Engineers
- AWWA - American Water Works Association
- DI - Ductile Iron
- EPDM - Ethylene Propylene Diene Monomer
- FL - Flange
- MJ - Mechanical Joint
- WAF - Wafer
- FF - Flange x Flange
- MF - Mechanical Joint x Flange
- WW - Wafer


Type	SAV Ref. #	Size	Weight kg lb		Price US \$
Model B88 FLxFL Rotork Gearbox Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, Flanged ends to ASME B 16.42, class 150 250 PSI Single direction testing Size 3"-24"	B88-080FFRGB-H1	3"	21	45	998
	B88-100FFRGB-H1	4"	26	57	1,110
	B88-150FFRGB-H1	6"	33	72	1,140
	B88-200FFRGB-H1	8"	53	116	1,460
	B88-250FFRGB-H1	10"	73	159	2,015
	B88-300FFRGB-H1	12"	95	209	2,410
	B88-350FFRGB-H1	14"	120	264	3,950
	B88-400FFRGB-H1	16"	157	346	4,690
	B88-450FFRGB-H1	18"	220	484	5,270
	B88-500FFRGB-H1	20"	259	569	7,090
	B88-600FFRGB-H1	24"	357	787	9,840
	Specify above ground, or below ground intallation when ordering				
Model B88 FLxFL Rotork Gearbox Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, Flanged ends to ASME B 16.42, class 150 250 PSI Bi-directional testing Size 3"-24"	B88-080FFRGB-H2	3"	21	45	1,198
	B88-100FFRGB-H2	4"	26	57	1,332
	B88-150FFRGB-H2	6"	33	72	1,368
	B88-200FFRGB-H2	8"	53	116	1,752
	B88-250FFRGB-H2	10"	73	159	2,418
	B88-300FFRGB-H2	12"	95	209	2,892
	B88-350FFRGB-H2	14"	120	264	4,740
	B88-400FFRGB-H2	16"	157	346	5,628
	B88-450FFRGB-H2	18"	220	484	6,324
	B88-500FFRGB-H2	20"	259	569	8,508
	B88-600FFRGB-H2	24"	357	787	11,808
	Specify above ground, or below ground intallation when ordering				
Model B88 MJxFL Rotork Gearbox Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, Flanged ends to ASME B 16.42, class 150 250 PSI Single direction testing Size 6"-24"	B88-150MFRGB-H1	6"	34	73	1,140
	B88-200MFRGB-H1	8"	53	115	1,460
	B88-250MFRGB-H1	10"	73	160	2,015
	B88-300MFRGB-H1	12"	91	200	2,410
	B88-350MFRGB-H1	14"	122	296	3,950
	B88-400MFRGB-H1	16"	164	360	4,690
	B88-450MFRGB-H1	18"	232	511	5,270
	B88-500MFRGB-H1	20"	273	601	7,090
	B88-600MFRGB-H1	24"	379	835	9,840
	Specify above ground, or below ground intallation when ordering				
Model B88 MJxFL Rotork Gearbox Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, Flanged ends to ASME B 16.42, class 150 250 PSI Bi-directional testing Size 6"-24"	B88-150MFRGB-H2	6"	34	73	1,368
	B88-200MFRGB-H2	8"	53	115	1,752
	B88-250MFRGB-H2	10"	73	160	2,418
	B88-300MFRGB-H2	12"	91	200	2,892
	B88-350MFRGB-H2	14"	122	296	4,740
	B88-400MFRGB-H2	16"	164	360	5,628
	B88-450MFRGB-H2	18"	232	511	6,324
	B88-500MFRGB-H2	20"	273	601	8,508
	B88-600MFRGB-H2	24"	379	835	11,808
	Specify above ground, or below ground intallation when ordering				

Type

**Model B88 MJxMJ
Rotork Gearbox
Ductile Iron**

To AWWA C504
Concentric butterfly valve,
Vulcanized rubber liner,

250 PSI
Single direction testing
Size 4"-24"



SAV Ref. #

Size

Weight
kg lb


Price
US \$

B88-100MMRGB-H1	4"	24	53	1,110
B88-150MMRGB-H1	6"	33	73	1,140
B88-200MMRGB-H1	8"	50	110	1,460
B88-250MMRGB-H1	10"	67	148	2,015
B88-300MMRGB-H1	12"	82	179	2,410
B88-350MMRGB-H1	14"	119	261	3,950
B88-400MMRGB-H1	16"	162	357	4,690
B88-450MMRGB-H1	18"	240	528	5,270
B88-500MMRGB-H1	20"	283	624	7,090
B88-600MMRGB-H1	24"	395	870	9,840

**Model B88 MJxMJ
Rotork Gearbox
Ductile Iron**

To AWWA C504
Concentric butterfly valve,
Vulcanized rubber liner,

250 PSI
Bi-directional testing
Size 4"-24"




B88-100MMRGB-H2	4"	24	53	1,332
B88-150MMRGB-H2	6"	33	73	1,368
B88-200MMRGB-H2	8"	50	110	1,752
B88-250MMRGB-H2	10"	67	148	2,418
B88-300MMRGB-H2	12"	82	179	2,892
B88-350MMRGB-H2	14"	119	261	4,740
B88-400MMRGB-H2	16"	162	357	5,628
B88-450MMRGB-H2	18"	240	528	6,324
B88-500MMRGB-H2	20"	283	624	8,508
B88-600MMRGB-H2	24"	395	870	11,808

**Model B88 Wafer
Rotork Gearbox
Ductile Iron**

To AWWA C504
Concentric butterfly valve,
Vulcanized rubber liner,

250 PSI
Single direction testing
Size 3"-20"




B88-080WWRGB-H1	3"	15	32	1,120
B88-100WWRGB-H1	4"	18	38	1,320
B88-150WWRGB-H1	6"	23	49	1,360
B88-200WWRGB-H1	8"	34	75	1,670
B88-250WWRGB-H1	10"	46	101	2,220
B88-300WWRGB-H1	12"	52	114	2,620
B88-350WWRGB-H1	14"	72	157	4,150
B88-400WWRGB-H1	16"	101	222	4,900
B88-450WWRGB-H1	18"	155	341	5,475
B88-500WWRGB-H1	20"	188	413	7,925





**Model B88 Wafer
Rotork Gearbox
Ductile Iron**

To AWWA C504
Concentric butterfly valve,
Vulcanized rubber liner,

250 PSI
Bi-directional testing
Size 3"-20"



B88-080WWRGB-H2	3"	15	32	1,110
B88-100WWRGB-H2	4"	18	38	1,110
B88-150WWRGB-H2	6"	23	49	2,052
B88-200WWRGB-H2	8"	34	75	2,628
B88-250WWRGB-H2	10"	46	101	3,627
B88-300WWRGB-H2	12"	52	114	4,338
B88-350WWRGB-H2	14"	72	157	7,110
B88-400WWRGB-H2	16"	101	222	8,442
B88-450WWRGB-H2	18"	155	341	9,486
B88-500WWRGB-H2	20"	188	413	12,762

Type		SAV Ref. #	Size	Weight		Price
				kg	lb	US \$
Model B88 FLxFL Above Ground Lever Operated Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, 150 PSI Single direction testing Size 3"-8"		B88-080FFLV-L1	3"	11	24	1,110
		B88-100FFLV-L1	4"	16	35	1,110
		B88-150FFLV-L1	6"	23	50	1,140
		B88-200FFLV-L1	8"	38	83	1,460
Model B88 FLxFL Above Ground Lever Operated Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, 150 PSI Bi-directional testing Size 3"-8"		B88-080FFLV-L2	3"	11	24	1,110
		B88-100FFLV-L2	4"	16	35	1,110
		B88-150FFLV-L2	6"	23	50	1,368
		B88-200FFLV-L2	8"	38	83	1,752
Model B88 Wafer Above Ground Lever Operated Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, 150 PSI Single direction testing Size 3"-8"		B88-080WWLV-L1	3"	5	10	840
		B88-100WWLV-L1	4"	8	16	990
		B88-150WWLV-L1	6"	13	27	1,020
		B88-200WWLV-L1	8"	18	40	1,253
Model B88 Wafer Above Ground Lever Operated Ductile Iron To AWWA C504 Concentric butterfly valve, Vulcanized rubber liner, 150 PSI Bi-directional testing Size 3"-8"		B88-080WWLV-L2	3"	5	10	1,110
		B88-100WWLV-L2	4"	8	16	1,110
		B88-150WWLV-L2	6"	13	27	2,052
		B88-200WWLV-L2	8"	18	40	2,628