

MODEL LD, AWWA C515

LARGE DIAMETER DUCTILE

Model LD AWWA Availability Listing

Size	FLxFL	MJxFL	MJxMJ
18"	X	X *	X
20"	X	X *	X
24"	X	X *	X
30"	X **	X **	X **
36"	X	X	X

* MJxFL Adaptor Kit on FLxFL valve and MJxFL can be used as tapping valve


** Integral Bypass Flanges on long lay length

AWWA C515, LARGE DIAMETER DUCTILE, RESILIENT WEDGE GATE VALVES

Type

**Model LD/FFN
LARGE DIAMETER C515
FLxFL**

Full wall ductile iron
Flanged ends to
ANSI B 16.1,
Class 150 NRS
250 PSI
Size 18", 20", 24", 30", 36"



SAV Ref. #

Size

**Weight
kg lb**

**Price
US \$**


LD-450-FFN	18"	599	1321	25,745
LD-500-FFN	20"	639	1408	30,919
LD-600-FFN	24"	856	1886	40,963
LD-800-FFN	30"	2404	5366	66,700
LD-900-FFN	36"	0780	8332	112,700

30" FLxFL available in lay lengths of 26" - Short, and 39" - Long. Long lay length has integral bypass flanges for mounting bypass valve assembly. Specify lay length when ordering.
All 30"-36" valves are supplied with actuation.

Use bid valve discount

**Model LD/MFN
LARGE DIAMETER C515
MJ X FL**

Full wall ductile iron
Mechanical joint end
X Flanged end to
ANSI B 16.1
Class 150 NRS
250 PSI
Size 18", 20", 24", 30", 36"



less MJ accessories


LD-450-MFN	18"	XXXX	XXXX	25,745
LD-500-MFN	20"	XXXX	XXXX	30,919
LD-600-MFN	24"	XXXX	XXXX	40,963
LD-800-MFN	30"	XXXX	XXXX	66,700
LD-900-MFN	36"	3812	8404	112,700

18", 20", 24", FLxFL valve with MJxFL adaptor, less MJ accessories
30", Integral bypass flanges
All 30"-36" valves are supplied with actuation.

Use bid valve discount

**Model LD/MMN
LARGE DIAMETER C515
MJxMJ**

Full wall ductile iron
Mechanical joint ends
NRS
250 PSI
Size 18", 20", 24", 30", 36"



less MJ accessories

LD-450-MMN	18"	603	1330	25,745
LD-500-MMN	20"	635	1400	30,919
LD-600-MMN	24"	847	1867	40,963
LD-800-MMN	30"	2472	5450	66,700
LD-900-MMN	36"	5151	11354	112,700


30", Integral bypass flanges
All 30"-36" valves are supplied with actuation.

Use bid valve discount

Type

Model LD/FFO/MO
LARGE DIAMETER C515
FLxFL OS&Y
MANUAL OPERATION

Full wall ductile iron
Flanged ends to
ANSI B 16.1,
Class 150 NRS
250 PSI
Size 18", 20", 24"



SAV Ref. #	Size	Weight		Price US \$
		kg	lb	
LD-450-FFO-MO	18"	599	1321	28,820
LD-500-FFO-MO	20"	639	1408	36,180
LD-600-FFO-MO	24"	856	1886	43,990

Use 14"-36" valve discount
For geared OS&Y valves refer to the Series 753 price adders

AWWA C515, LARGE DIAMETER DUCTILE, RESILIENT WEDGE GATE VALVES